



# WOOD & DECK

*WDA - CLEANER / WDB - BRIGHTENER*

**MESSMER'S WOOD & DECK CLEANER (Part A)** and **WOOD & DECK BRIGHTENER (Part B)** are powder concentrates designed to prepare exterior wood for staining. **WOOD & DECK CLEANER** removes dirt and gray from exterior wood surfaces. **WOOD & DECK BRIGHTENER** brightens wood surfaces after cleaning or stripping, enhances wood grain appearances, and restores wood's pH.

## PRODUCT TYPE

Powder concentrates, to be mixed with water before use  
WDA Cleaner contains Sodium Percarbonate  
WDB Brightener contains Oxalic Acid

## APPEARANCE

White granular (WDA) or crystalline (WDB) powder

## VOC CONTENT

WDA 0 grams / liter  
WDB 0 grams / liter

## SOLIDS BY VOLUME AND WEIGHT

WDA 100%  
WDB 100%

## COVERAGE

Up to 600 square feet per pound when mixed with water. Tougher jobs may require a second application, or more concentrated mixing.

## DRY TIME

Allow at least 24-48 hours dry time before staining after cleaning and/or brightening with WDA or WDB.

WDB may be used immediately after rinsing WDA

## APPLY WITH

Garden sprayer, mop or plastic bristle brush

## PACKAGING

One pound jars

## INSTRUCTIONS

### SURFACE PREPARATION

Remove dirt and debris from wood surfaces before proceeding

### SPECIAL INSTRUCTIONS

Dissolve approximately 1/3 cup of powder in one gallon of hot water and mix well. Mix in a plastic bucket. Once mixed, products should be used promptly.

### WDA Cleaner

Mix according to label directions. Apply with a garden sprayer, mop or brush. Allow product to soak on wood briefly. Agitate with a stiff brush or push broom. Rinse thoroughly with clean water.

### WDB Brightener

Mix according to label directions. Apply to cleaned and rinsed wood. Allow product to dwell on wood surface for 10-15 minutes, then rinse thoroughly with clean water. After application and rinsing, immediately flood surrounding vegetation with generous amounts of water.

### CLEANUP

Clean tools and brushes with water

### PRECAUTIONS

Keep out of the reach of children. Mix in plastic containers. To prevent corrosion do not allow products to dwell on unpainted aluminum or steel. Follow all label directions.