

MESSMER'S

NATURAL WOOD FINISHES



MOSO[®] Bamboo Finish

NATURAL

Messmer's MOSO[®] Bamboo Finish is an oil based penetrating natural finish specifically designed for use on exterior MOSO[®] Bamboo and hardwoods. MOSO[®] Bamboo Finish protects and conditions MOSO[®] Bamboo and wood surfaces while maintaining a completely natural appearance.

SPECIFICATIONS

VEHICLE TYPE

Solvent and VOC exempt solvent borne blend of oils and alkyds

COLORS

Available in Natural, a lightly pigmented transparent finish

VISCOSITY

15-18 seconds Zahn #2 at 77F

VOC CONTENT

<250 g/L (as supplied)

SOLIDS BY VOLUME

49%

SOLIDS BY WEIGHT

48%

WEIGHT PER GALLON

7.5 lbs

COVERAGE

Rough Surface: 150 to 250 square feet per gallon

Smooth Surface: 200 to 300 square feet per gallon

DRY TIME

Allow 24 hours in good drying conditions

APPLY WITH

Brush, applicator pad, airless sprayer

PACKAGING

One gallon containers

SURFACE PREPARATION

Always clean gray or dirty bamboo or wood before applying MOSO[®] Bamboo Finish. Use Messmer's Part A Wood and Deck Cleaner. Allow surface to completely dry for at least 24 to 48 hours. Previously stained or treated surface should be sufficiently weathered to allow for complete penetration.

SPECIAL INSTRUCTIONS

Before applying, this product should be mixed thoroughly. Ensure that all settled material on bottom of can is evenly incorporated, and intermix all containers (box them).

Apply MOSO[®] Bamboo Finish when surface temperatures are between 45F and 90F. If surface is hot to the touch, it is too hot to apply product. Do not apply product if precipitation is expected within 24-48 hours.

Spray Application: When spraying, back brush to prevent sags and runs. Cover surrounding areas to protect from overspray. For airless spray, use .015" to .019" tip size.

Brush Application: To minimize lapping, maintain a wet edge lengthwise and do not break in the middle of boards.

One coat is sufficient for most applications. Product not absorbed into the surface within 30 minutes must be removed to prevent surface sheen.

THINNING RECOMMENDATIONS

Thinning is not recommended.

CLEANUP

Use paint thinner. Dispose of waste in accordance with local, state and federal regulations.

MORE INFO

Visit messmers.com/moso

Danger - Rags, steel wool or waste soaked with this product may spontaneously catch fire if improperly discarded. Immediately after each use, place rags, steel wool or waste in a sealed, water filled metal container.