

MESSMER'S

NATURAL WOOD FINISHES



SIMPLE SEAL

By Messmer's

Beautifies and Protects Exterior Wood

DESCRIPTION: SIMPLE SEAL by Messmer's provides lasting beauty and protection to exterior wood surfaces. The easy to use formula protects wood with water repellents, UV absorbers, and fungicides. **SIMPLE SEAL by Messmer's** is easy to use, with a low VOC formula that's emissions compliant in all states and counties.

SPECIFICATIONS

VEHICLE TYPE

Solvent borne oil system

COLORS

Available in six attractive colors:

SS-900 Natural
SS-901 Redwood
SS-902 Pecan
SS-903 Walnut
SS-904 Mission
SS-909 Slate

VOC CONTENT

<100 grams per liter (as supplied)

SOLIDS BY VOLUME

Approximately 90% by volume

SOLIDS BY WEIGHT

Approximately 90% by weight

WEIGHT PER GALLON

7.1 pounds

COVERAGE

Smooth wood: 175 to 250 square feet per gallon
Rough wood: 100 to 175 square feet per gallon

DRY TIME

Allow 24-48 hours in good drying conditions. Product will continue to dry for several days before final color and appearance are achieved.

APPLY WITH

Brush, roller, airless sprayer

PACKAGING

One gallon cans, five gallon pails

SURFACE PREPARATION

Make sure surface is free of dirt, mildew, dust, oil and waxes, and is structurally sound and dry. Any loose or peeling previous finish must be removed before application. Clean surface with Messmer's Wood & Deck Cleaner and Brightener products.

SPECIAL INSTRUCTIONS

Before applying, this product should be mixed thoroughly. Ensure that all settled material on bottom of can is evenly incorporated, and intermix all containers (box them).

Apply SIMPLE SEAL by Messmer's when surface temperatures are between 45F and 90F. If surface is hot to the touch, it is too hot to apply product. Do not apply product if precipitation is expected within 24-48 hours.

Spray application: When spraying, back brush or roll to prevent sags and runs. Cover surrounding areas to protect from overspray.

Brush application: To minimize lapping, maintain a wet edge lengthwise and do not break in the middle of boards.

One coat is sufficient for most applications.

MAINTENANCE

Clean wood with Messmer's Wood and Deck Cleaner and Brightener, then allow to dry. Apply SIMPLE SEAL by Messmer's per label directions.

THINNING RECOMMENDATIONS

Thinning is not recommended.

CLEANUP

Use paint thinner (mineral spirits). Dispose of waste, empty containers and unused product in accordance with local, state and federal regulations.