



DESCRIPTION: **TIMBERFLEX PRO** is a premium two coat finish for exterior vertical surfaces including log and timber homes and wood siding. **TIMBERFLEX PRO** protects wood with a beautiful translucent satin finish.

SPECIFICATIONS

VEHICLE TYPE

Solvent based, blend of alkyd resins

COLORS

Natural, Natural Pine / Fir, Natural Cedar, Natural Redwood, Sequoia, Navajo Red, Oxford Brown, Dark Walnut, Oak Brown

GLOSS LEVEL

Satin

VOC CONTENT

TFP Series <275 grams per liter (as supplied)

SOLIDS BY VOLUME

TFP Series 60%

SOLIDS BY WEIGHT

TFP Series 64%

WEIGHT PER GALLON

8.5 to 9.0 pounds

COVERAGE

First coat: 200-250 square feet per gallon
Second Coat: 250 to 300 square feet per gallon

DRY TIME

Allow 24 hours in good drying conditions

APPLY WITH

Brush, roller, airless sprayer

PACKAGING

One gallon and five gallon containers.

SURFACE PREPARATION

Always clean gray or dirty wood before applying Timberflex PRO. Use Messmer's WD Wood and Deck products, available in powder concentrates. Allow wood to completely dry for at least 24 to 48 hours.

SPECIAL INSTRUCTIONS

Before applying, this product should be mixed thoroughly. Ensure that all settled material on bottom of can is evenly incorporated, and intermix all containers (box them).

Apply Timberflex PRO when surface temperatures are between 45F and 90F. If surface is hot to the touch, it is too hot to apply product. Do not apply product if precipitation is expected within 24-48 hours.

Spray application: When spraying, back brush or roll the first coat to prevent sags and runs. Cover surrounding areas to protect from overspray. For airless spray, use .017" to .019" tip for best results.

Brush application: To minimize lapping, maintain a wet edge lengthwise and do not break in the middle of boards.

Two coats are sufficient for most applications. Additional coats will provide deeper color and additional wood protection.

MAINTENANCE

A maintenance coat of TIMBERFLEX PRO should be applied as needed to maintain appearance. The time interval will vary with exposure, direction, altitude and local climate, but a general guideline is every two to three years.

THINNING RECOMMENDATIONS

Thinning is not recommended. If allowed by local environmental regulations, mineral spirits may be used.

CLEANUP

Use paint thinner (mineral spirits). Dispose of waste in accordance with local, state and federal regulations. **Danger – Rags, steel wool or waste soaked with this product may spontaneously catch fire if improperly discarded. Immediately after each use, place rags, steel wool or waste in a sealed, water filled metal container.**